

MANGO65S Series

65 Watt Medical Desktop
Power Supply

PHASIUM

BY MEGMEET

Medical Power Specialists



The supply chain solution for reliability and low cost. The **MANGO65S** series meets all Medical and Commercial compliance requirements including 4th Edition EMC and Level VI Efficiency. **MANGO65S** adapters feature user-definable IEC 320 Inlet plug styles for Class I and Class II installation options and standard DC outputs from 12V to 48V.

Key Features

- Medical 60601-1 Safety Approvals
- Small 4.17 x 2.24 x 1.14" Footprint
- Class I or Class II Construction
- IPX1 Rated Enclosure
- High Efficiency - Level VI
- High Power Density - 5.63W/in³
- CEC 2008 / ErP2 / EISA 2007 Compliant
- EN55011 / FCC Part 15J Class B Emissions
- 3 Year Warranty



Medical Lighting



Battery Charger



Portable Monitor



Sleep Apnea Therapy


PHASIUM
BY MEGMEET

POWER@PHASIUMPOWER.COM


Models	Output Voltage	Output Current	Peak Current	Ripple & Noise (Max)
MANGO065S-12xy	12V	5.4A	6.0A	120mV
MANGO065S-19xy	19V	3.4A	3.8A	190mV
MANGO065S-24xy	24V	2.7A	3.0A	240mV
MANGO065S-28xy	28V	2.3A	2.6A	280mV
MANGO065S-48xy	48V	1.4A	1.5A	480mV

For the given model, replace "xy" with selected AC Inlet and DC Plug options. See product family application notes for details.


Technical Highlights			
Input Voltage	90~264 VAC (Universal) 300 VAC (maximum Non-Operating)	Efficiency	89% typical at 115/230 VAC, full load
Leakage Current	<100µA @ 264VAC	Operating Temperature	0°C ~ +40°C
Output Voltage	See table above	Over Voltage	110~140% Latching
Line Regulation	±1%	MTBF	200K Hours, Mil-217F at 25 °C, full load
Load Regulation	±5%	Isolation	4000 VAC – Input to Output 1500 VAC – Input to Ground 500 VDC – Output to Ground



Note: Product specifications are subject to change without prior notice.




A - C14 Inlet / Class I Safety Approvals



B - C8 Inlet / Class II Safety Approvals

TYPE "B" CONNECTOR:
5.5 x 2.5 x 11 mm Barrel Jack



TYPE "K" CONNECTOR:
Part # Kycon KPPX-4P

